



E. I. du Pont de Nemours and Company Washington Works Mail: P.O. Box 2800 Washington, WV 26181-2800

October 21, 2016

CERTIFIED MAIL - 7007 1490 0001 6676 7951 RETURN RECEIPT REQUESTED

Mr. W. Fred Durham, Director Division of Air Quality WV Department of Environmental Protection 601 57th Street Charleston, WV 25304

RE: Permit Determination Request for Replacement of Salt Tanks, R13-0985

Dear Mr. Durham:

With this letter DuPont requests a permit determination regarding a 2015 replacement in-kind for a pair of storage tanks in the Salt Section of the Zytel® nylon resins production facility covered by permits R13-0985 and R30-10700001-2011 Segment 5 of 14.

The only changes needed for the Title V permit are updates to the tank descriptions in the Emission Units table. The corrections have been described in the permit renewal process which is nearing completion.

Should you have any questions or concerns regarding the actions described in this letter or any related matter, please contact me at 304-863-2202 or Chris Shoop at 304-863-2133.

Very truly yours, Thanks R. ILL

C. R. Hill

SHE Manager

**DuPont Washington Works** 

**ENCLOSURE** 

CRH:ces/kdf

Copy: Michael Egnor, Permitter, WV DAQ 🗸

Denton McDerment, Permitter, WD DAQ (cover only)



#### WEST VIRGINIA DEPARTMENT OF ENVIRONMENTAL PROTECTION DIVISION OF AIR QUALITY 601 57th Street, SE Charleston, WV 25304

PERMIT	DETERMINATION	<b>FORM</b>
	(PDF)	

FOR AGENCY USE ONLY: PLANT I.D. # Phone: (304) 926-0475 www.dep.wv.gov/daq PDF#\_ PERMIT WRITER: NAME OF APPLICANT (AS REGISTERED WITH THE WV SECRETARY OF STATE'S OFFICE): E. I. du Pont de Nemours and Company NAME OF FACILITY (IF DIFFERENT FROM ABOVE): NORTH AMERICAN INDUSTRY CLASSIFICATION SYSTEM (NAICS) Washington Works 3252111 4A. MAILING ADDRESS: 4B. PHYSICAL ADDRESS: DuPont Washington Works **DuPont Washington Works** P.O. Box 2800 8480 DuPont Road, Building 24 Washington WV 26181 Washington WV 26181-1217 5A. DIRECTIONS TO FACILITY (PLEASE PROVIDE MAP AS ATTACHMENT A): See Map - From Charleston take I-77 north to the Route 50. Turn West on to Route 50 and use the bypass around Parkersburg. At the DuPont Road Exit - exit and at DuPont Road turn Left. The plant is approximately 14 - 1/2 mile on the right side. 5B. NEAREST ROAD: 5C. NEAREST CITY OR TOWN: 5D. COUNTY: DuPont Road Parkersburg Wood 5E. UTM NORTHING (KM): 5F. UTM EASTING (KM): 5G. UTM ZONE: 4346.8331 442.3767 17 6A. INDIVIDUAL TO CONTACT IF MORE INFORMATION IS REQUIRED: 6B. TITLE: Charles R. Hill SHE Manager 6C. TELEPHONE: 6D. FAX: 6E. E-MAIL: (304) 863-2202 (304) 863-2190 Charles-R.F.Hill-1@dupont.com 7A. DAQ PLANT I.D. NO. (FOR AN EXISTING FACILITY ONLY): 7B. PLEASE LIST ALL CURRENT 45CSR13, 45CSR14, 45CSR19 AND/OR TITLE V (45CSR30) PERMIT NUMBERS ASSOCIATED WITH THIS PROCESS (FOR AN EXISTING FACILITY ONLY): 107 - 00001 R13-0985 R30-10700001 Part 5 of 14 7C. IS THIS PDF BEING SUBMITTED AS THE RESULT OF AN ENFORCEMENT ACTION? IF YES, PLEASE LIST: 8A. TYPE OF EMISSION SOURCE (CHECK ONE): 8B. IF ADMINISTRATIVE UPDATE, DOES DAQ HAVE THE APPLICANT'S CONSENT TO UPDATE THE EXISTING ☐ NEW SOURCE ■ ADMINISTRATIVE UPDATE PERMIT WITH THE INFORMATION CONTAINED HEREIN? ☐ MODIFICATION **⊠** YES □ NO OTHER (PLEASE EXPLAIN IN 11B) IS DEMOLITION OR PHYSICAL RENOVATION AT AN EXISTING FACILITY INVOLVED? YES **⋈** NO 10A. DATE OF ANTICIPATED INSTALLATION OR CHANGE: 10B. DATE OF ANTICIPATED START-UP: As Built As Built 11A. PLEASE PROVIDE A DETAILED PROCESS FLOW DIAGRAM SHOWING EACH PROPOSED OR MODIFIED PROCESS EMISSION POINT AS ATTACHMENT B. 11B. PLEASE PROVIDE A **DETAILED PROCESS DESCRIPTION** AS **ATTACHMENT C**. 12. PLEASE PROVIDE MATERIAL SAFETY DATA SHEETS (MSDS) FOR ALL MATERIALS PROCESSED, USED OR PRODUCED AS ATTACHMENT D. FOR CHEMICAL PROCESSE, PLEASE PROVIDE A MSDS FOR EACH COMPOUND EMITTED TO AIR.

#### 13A. REGULATED AIR POLLUTANT EMISSIONS:

⇒ FOR A NEW FACILITY, PLEASE PROVIDE PLANT WIDE EMISSIONS BASED ON THE POTENTIAL TO EMIT (PTE) FOR THE FOLLOWING AIR POLLUTANTS INCLUDING ALL PROCESSES.

⇒ FOR AN EXISTING FACILITY, PLEASE PROVIDE THE PROPOSED CHANGE IN EMISSIONS BASED ON THE PTE OF ALL PROCESS CHANGES FOR THE FOLLOWING AIR POLLUTANTS.

PTE FOR A GIVEN POLLUTANT IS TYPICALLY <u>BEFORE AIR POLLUTION CONTROL DEVICES</u> AND IS COLLECTED BASED ON THE MAXIMUM DESIGN CAPACITY OF PROCESS EQUIPMENT.

POLLUTANT	HOURLY PTE (LB/HR)	YEARLY PTE (TON/YR) (HOURLY PTE MULTIPLIED BY 8760 HR/YR) DIVIDED BY 2000 LB/TON  0.00034		
PM	Not Applicable			
PM <sub>10</sub>	Not Applicable	0.00034		
VOCs	Not Applicable	0.00034		
со	0	0.		
NO <sub>x</sub>	0	0		
SO <sub>2</sub>	0	0		
Pb	0	0		
HAPs (AGGREGATE AMOUNT)	0	0		
TAPs (INDIVIDUALLY)*	0	0		
OTHER (INDIVIDUALLY)*	0	0		

<sup>\*</sup> ATTACH ADDITIONAL PAGES AS NEEDED

## 13B. PLEASE PROVIDE ALL SUPPORTING CALCULATIONS AS ATTACHMENT E.

CALCULATE AN HOURLY AND YEARLY PTE OF EACH PROCESS EMISSION POINT (SHOWN IN YOUR DETAILED PROCESS FLOW DIAGRAM) FOR ALL AIR POLLUTANTS LISTED ABOVE INCLUDING INDIVIDUAL HAP'S (LISTED IN SECTION 112[b] OF THE 1990 CAAA), TAP'S (LISTED IN 45CSR27), AND OTHER AIR POLLUTANTS (E.G. POLLUTANTS LISTED IN TABLE 45-13A OF 45CSR13, MINERAL ACIDS PER 45CSR7, ETC.).

#### 14. CERTIFICATION OF DATA

I, <u>JAY VALVO</u> (*TYPE NAME*) ATTEST THAT ALL THE REPRESENTATIONS CONTAINED IN THIS APPLICATION, OR APPENDED HERETO, ARE TRUE, ACCURATE, AND COMPLETE TO THE BEST OF MY KNOWLEDGE BASED ON INFORMATION AND BELIEF AFTER REASONABLE INQUIRY, AND THAT I AM A *RESPONSIBLE OFFICIAL\*\** (*PRESIDENT, VICE PRESIDENT, SECRETARY OR TREASURER, GENERAL PARTNER OR SOLE PROPRIETOR*) OF THE APPLICANT.

SIGNATURE OF RESPONSIBLE OFFICIAL:

TITLE: PLANT MANAGER

DATE: 10, 120, 16

\*\*THE DEFINITION OF THE PHRASE 'RESPONSIBLE OFFICIAL' CAN BE FOUND AT 45CSR13, SECTION 2.23.

NOTE: PLEASE CHECK ENCLOSED ATTACHMENTS:


oxtimes ATTACHMENT A oxtimes ATTACHMENT B oxtimes ATTACHMENT C oxtimes ATTACHMENT D oxtimes ATTACHMENT E Records on all changes are required to be kept and maintained on-site for two (2) years.

THE PERMIT DETERMINATION FORM WITH THE INSTRUCTIONS CAN BE FOUND ON DAQ'S PERMITTING SECTION WEB SITE:

www.dep.wv.gov/dag

### ATTACHMENT A

# MAP to the Facility



From Interstate 77, take exit for Rt-95/Camden Avenue.

Proceed West until intersection with Rt-14 then turn right (north).

After about 1/4 mile turn left onto Corridor D Bypass entrance for US-50 West.


Follow the bypass to the exit just before the bridge.

Turn left (south) onto DuPont Rd, Rt-892.

Proceed approx. 1 mile to facility on right.


## **ATTACHMENT B**

## Process Flow Diagram



The process flow diagram is from the application for R13-0985 which was submitted December 11, 1987. The permit was approved on January 21, 1988. The process has not been changed since that time except that Tanks 13-14 were replaced in-kind in 2015 using the previously existing Tanks 11-12.

Tanks 11-12 are identical to the previous tanks 13-14. The vessel is a horizontal cylinder with two separate chambers separated by a wall at the mid-point. It is insulated with internal circulation and is temperature controlled at 70C. The vapor space is inerted using nitrogen. The conservation vent is set at +0.826 psia and -0.125 psia.



#### ATTACHMENT C

## Process/Project Description

The purpose of this request is to provide corrected identification for the tanks that were replaced in-kind for permit R13-0985 and for Title V permit R30-10700001 Part 5 of 14. The emission unit ID in both permits is 155-T14S. We propose that the change does not require a change to R13-0985 but we propose that the emission unit descriptions in the Title V permit should be updated to reflect the use of the replacement tanks.

A permit determination request was submitted in 1998 to recalculate the emissions from the unit, including the tanks, to describe the emitted material 1,6-hexanediamine, (hexamethylene diamine or HMD) as a particulate, consistent with the emitted form for this high boiling point chemical. The revised calculation also more appropriately addressed the vapor pressure for HMD and showed reduced potential emissions. Permit determination PD98-172 was issued on August 28, 2001 declared that no change to the permit was necessary but listed the revised potential emissions.

The annual limit expressed in R13-0985 for emission point 155-T14S was 267 lb/year (0.14 tons/year) of HMD. This estimate was based on the partial pressure of HMD expected and the volumes of salt solution transferred through the vessels. The estimate in the 1998 permit determination was reduced to 0.45 lb/yr (0.00023 tpy) based on use of EPA's AP-42 then current tank calculations. The present estimated emissions are 0.68 lb/yr (0.00034 tpy), based on the current operating conditions and use of EPA's Tanks 4.09 software application.

NSPS Subpart Kb for storage tanks does not apply to the replacement of this vessel. Although the combined capacity of the two compartments (29,800 gal or 110.5 m^3) is above the volume threshold of 75 cubic meters, the maximum true vapor pressure for the vessel (0.00013 psia or 0.0009 kPa) is below the applicability threshold of 15.0 kPa.

#### **ATTACHMENT E**

#### Calculations

The inputs calculated below were used in US EPA Tanks 4.09 estimation tool.

HMD Emission Calculations for Tanks 11-12

Mol Wt

HMD 116.2 DDDA 230.3

Salt 346.5

At pH=8 the solution will have 16 equivalents of HWM per 10^6 grams of salt in solution.

Mol Ratio at 16 eq/megagram

16 eq HMD per 10^6 g salt \* [1 mol HMD per 2 equiv] \* 346.5 g per mol salt

mol ratio 0.002772

Convert to 45% solution

Salt conc

45%

mol fract

0.0012474

Partial pressure

HMD @ 70C

**0.106** psia

DIPPR database (2014)

p = pi \* xi

(VP 100%) (mol fract)

р

0.000132224

Turnovers

=6000 \* 8760 hrs / 9.05 lb/gal / 29200 gal

198.8950276

Turnovers

200

#### **TANKS 4.0.9d Emissions Report - Detail Format**

## Tank Indentification and Physical Characteristics

Iden	uf cati	OF

User Identification: User Identificat City: State: Company: Type of Tank: Description:

Tank 11-12 Charleston West Virginia DuPont Horizontal Tank 6,12 salt Horizontal Heated

Tank Bimensions
Shall Length (ft):
Diameter (ft):
Volume (gallons):
Tumovers:
Net Throughput (gallyr):
is Tank Heated (y/n):
Is Tank Underground (y/n):

48.00 10.00 29,200.00 200.00 5,640,000.00

Paint Characteristics Shell Color/Shade: Shell Condition

Aluminum/Diffuse Good

Breather Vent Settings Vacuum Settings (psig): Pressure Settings (psig)

Meterological Data used in Emissions Calculations: Charleston, West Virginia (Avg Atmospheric Pressure = 14.25 psia)

### **TANKS 4.0.9d Emissions Report - Detail Format** Liquid Contents of Storage Tank

Tank 11-12 - Horizontal Tank Charleston, West Virginia

			My Liquid S perature (d		Liquid Bulk Temp	Vapo	n Pressure	(psia)	Vapor Not.	Liquid Mass	Vapor Mass	Mal.	Basis for Vapor Pressure	
Michel Cortponent	Mantin	Avg	Min.	Max	(deg F)	AVG.	Min.	Mag	Weight	Fract.	Fract.	Weight	Calculations	
5,12 Salt at pH 8	д	8237	53.24	71.50	57.56	0.0001	0.0001	0.9001	118,0000			1141.00		

## TANKS 4.0.9d Emissions Report - Detail Format Detail Calculations (AP-42)

#### Tank 11-12 - Horizontal Tank Charleston, West Virginia

Annual Emission Calcaulations	
Standing Losses (lip):	
Vapor Space Volume (cu ft):	6.0077
Vapor Density (Ip/ou ft):	2,401,2173
Vapor Space Expansion Factor:	0.0006
	0.0030
Versied Vapor Saturation Factor	1,0000
Tank Vapor Space Volume:	
Vapor Space Volume (ou 8):	2461,2178
Tank Diameter (%):	10,0000
Effective Diameter (ft):	24.7278
Vapor Space Cutage (fil):	5,0000
Tank Shell Length (ft):	46,0000
Vator Density	
Vapor Bensity (lb/ou ft):	0.0000
Vapor Niclecular Weight (Ib/Ib-mote):	0.0000
	116,0000
Vapor Pressure at Daily Average Liquid	
Sulface Temperature (pula):	0.0001
Daily Avg. Liquid Surface Temp. (deg. R):	522,0370
Daily Average Ambient Temp. (deg. F):	64.9831
Ideal Gas Constant R	
(psia out) / (lo-mol-deg R)):	10,731
Liquid Bulk Temperature (deg. R):	5 : 7.2533
Tank Faint Solar Absorptance (Shell):	0.6000
Daily Total Solar Insulation	
Factor (Bhu/soft day):	1,250.5726
Vapor Space Expansion Factor	
Vapov Space Expansion Factors	0.0032
Daily Vapor Temperature Range (deg. R);	36,5136
Dally Vapor Fressure Range (pela):	0.0000
Breather Verit Presix, Setting Range(polat);	0.9510
Vapor Pressure at Daily Average Liquid	0.9310
Surface Temperature (osla):	
Vapor Pressure at Daily Minimum Liquid	0.0001
Surface Temperature (psia):	0.500
Vapor Pressure at Clairy Maximum Liquid	0.0001
Surface Temperature (pala):	0.0001
Daily Avg. Liquid Surface Temp. (deg R):	522.0370
Daily Mrs. Liquid Surface Terrol. (deg R):	512,9088
Daily Max. Liquid Surface Temp. (deg R):	531.1855
Daily Ambleot Temp. Range (dag. R):	21.5333
Verhed Vapor Saturation Factor	
Vertied Vapor Saturation Factor:	1,0000
Vapor Pressure at Dbilly Average Liquid:	
Surizos Temperature (psia):	0.0001
Vapor Space Outage (R):	5,0000
Working Losses (lo);	0.6742
Vapor Molecular Weight (Mith-mole):	116,0000
Vapor Pressure at Dally Average Liquid	1.0.5455
Surface Temperature (p.sia):	0.0061
Attnust Net Toroughput (gallyr.):	5,840,000,0000
Angual Turkgyers	200,0000
Tumover Factor:	0.3187
Tank Diameter (E):	0.0000
Working Loss Product Factor:	
Tremen poses i regione i dibilità.	1.0000
Trials	200
Total Losses (b):	0.6819

## TANKS 4.0.9d Emissions Report - Detail Format Individual Tank Emission Totals

## Emissions Report for: Annual

Tank 11-12 - Horizontal Tank Charleston, West Virginia

	Losses(lbs)							
Components	Working Loss	Breathing Loss	Total Emissions					
6,12 Salt at pH 8	0.67	0.01	0.56					